


RWWD46 Silicone Radiator

Heavy duty softwall radiator hose recommended for conveying hot water, steam and anti-freeze, etc in cooling systems, used in automobiles. Resistant to heat, ageing and moderate oil resistance.

Tube:	Red, heat resistant synthetic silicone rubber compound
Cover:	Blue, smooth wrapped finish rubber compound
Reinforcement:	High strength synthetic cord
Temperature:	-40°C to +200°C
Conforming Standards:	SAE J20 R1
Branding:	



Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
19	19.1	27.2	160	480	0.35
22	22.2	30.4	155	465	0.38
25	25.4	33.5	150	450	0.47
28	28.1	36.7	145	435	0.49
32	32.1	39.9	140	420	0.52
35	33.3	43.1	135	405	0.57
38	38.1	46.2	125	375	0.61
41	41.3	49.4	115	345	0.82
45	44.5	52.6	100	300	0.83
51	50.8	59.9	80	240	1.11
54	53.9	62.1	80	225	1.19
57	57.1	65.3	75	225	1.26
60	60.3	68.5	70	210	1.29
63	63.5	71.6	65	195	1.33
67	66.7	76.0	65	195	1.43
70	69.9	78.0	65	195	1.50
76	76.1	84.3	65	195	1.68
90	88.9	97.0	50	150	2.18
102	101.6	109.7	40	120	2.22
127	127.0	135.1	30	90	3.40

DS-RWWD46

REV: OCTOBER 2020