

Receiver
From

 Society
 Reference
 Address
 Phone
 Fax
 E-mail

Item n° :

504100412

Model :

S4B-8 M 230 V

Pump data

Pressure rating :

Min. fluid temperature : 0 °C

Max. fluid temperature : 40 °C

Max. Temperature operating :

Requested data

Flow : 0 m³/h

Head : 0 m

Fluid : Water, pure

Fluid Temperature : 20 °C

Density : 998.3 kg/m³

Kinematic viscosity : 1.005 mm²/s

Vapor pressure : 100 kPa

Hydraulic data (duty point)

Flow :



Head :

Materials

Lower support	AISI 304 micro use
Impeller	Technopolymer A / AISI 304
Diff user	Technopolymer A
Impeller Lock nut	Stainless steel
Cable cover	AISI 304 X5 Cr Ni 1810 UNI 6900/71
Shaft with rotor	AISI 304 X5 Cr Ni 1810 UNI 6900/71
Filter	Stainless steel

Motor data

Motor brand :	TESLA	
Nominal power P2:	0.37 kW	
Rated voltage :	1~ 230 V	50 Hz
Nominal current :	3.3 A	
Number of poles :	2	
Rated speed :	2820 rpm	
Degree of protection :	IP 68	


Weight : 12.1 kg

Dimensions in mm

Dimension	Value	Unit			
DNM	1"1/4 G-F				
H	598				
Ø	97				


Pump connection

Suction side	/
Discharge side	1" 1/4 G-F / --

Society Reference Address Phone Fax E-mail	Receiver	From

S4B-8 M 230 V

Curve tolerance according to ISO 9906



Hydraulic data (duty point)

Suction side	Discharge side 1 " 1/4 G-F --	Flow : 0 m³/h	Head : 0 m	Rated speed : 2820 rpm
Project	Project ID	Created by	Created on 12/12/2014	



WATER • TECHNOLOGY

DIMENSIONAL DRAWING

12/12/2014

Page 3 / 3


DAB PUMPS S.p.A.
Via Marco Polo, 14 - 35035 Mestrino (PD), Italy
Tel. +39 049 5125000 - Fax +39 049 5125950
www.dabpumps.com

Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

S4B-8 M 230 V



Dimensions in mm

1	DNM	1"1/4 G-F
2	H	598
3	Ø	97

Pump connection

Suction

Discharge
1 " 1/4 G-F
-

Project

Project ID

Created by

Created on

12/12/2014