

# Self-Priming Inox Series

 230A   
  240A   
  250A

- Self-Priming
  - Very quiet
  - 304 stainless shaft
  - Multi-Staged
  - Constant Pressure
  - Loss of prime protection
  - Designed to auto-start and stop
- 🇮🇹 Designed in Italy

FL-4812663 INOX 230A  
 FL-5104073 INOX 240A  
 FL-5104074 INOX 250A

**3**  
YEAR  
WARRANTY



High performance in self-priming  
(8m in less than 3')



Model	230A	240A	250A	
<b>Electrical data</b>	P2 Pump consumption [W]	540	720	985
	Voltage [V]	1 ~ 240 AC	1 ~ 240 AC	1 ~ 240 AC
	Frequency [Hz]	50	50	50
	Current [A]	3.9	3.9	5.5
	Capacitor nF	12.5	12.5	20
	Capacitor Vc	450	450	450
<b>Hydraulic data</b>	Flow rate max. [l/min]	100	100	100
	Max. Pressure [Bar]	3.5	4.8	6.0
	Max. Head [m]	3.5	4.8	6.0
	Start pressure [bar]	1.8	2.2	2.2
	Stop pressure [bar]	3.2	3.2	3.2
	Max. working pressure [bar]	6	6	6
<b>Range of use/materials</b>	Max. suction depth [m]	8 m/3 min	8 m/3 min	8 m/3 min
	Length of Power Cable [m]	2.0	2.0	2.0
	Cable	H07 RNF	H07 RNF	H07 RNF
	Pump International protection	IP X4	IP X4	IP X4
	Insulation Class	F	F	F
	Pressure measure	Gauge	Gauge	Gauge
	Liquid range Temperature [°C]	0 °C / +35 °C	0 °C / +35 °C	0 °C / +35 °C
	Max. Ambient Temperature [°C]	+40 °C	+40 °C	+40 °C
<b>Dimensions / weight</b>	L x W x H [mm]	380 x 210 x 440	430 x 210 x 440	500 x 230 x 440
	Ldm [mm]	380	430	450
	Hda [mm]	440	440	440
	Wam [mm]	210	210	210
	Discharge Thread BSP	1" F	1" F	1" F
	Suction Thread BSP	1" F	1" F	1" F
	Box Dimensions l x w x h [cm]	56 x 27 x 35	56 x 27 x 35	56 x 27 x 35
	Net/Gross Weight [kg]	10.5 / 11.5	13 / 14	14.5 / 15.5
	Quantity for pallet [no.]	18	18	18

