

Drainage Dirty & Clear Water EcoSub 7

- Adjustable Free Passage
- Compact
- Manual and Automatic Mode
- Plug & Play
- 🇮🇹 Designed in Italy

FL-4819842



| | Model | EcoSub 7 |
|-------------------------------|---|------------------|
| Electrical data | P1 Power consumption [W] | 440 |
| | P2 Power consumption [W] | 210 |
| | Voltage [V] | 1 ~ 220-240 AC |
| | Frequency [Hz] | 50 |
| | Current [A] | 1.6 |
| | Capacitor nF | 8 |
| | Capacitor Vc | 450 |
| Hydraulic data | Flow rate max. [l/min] | 140 |
| | | 0,77 |
| | Max. Head [m] | 7 |
| | Max. Immersion depth [m] | 7 |
| | Min. depth of water for switching on (AUT) [mm] | 260 |
| | Min./Max. depth for switching off [mm] | 100/150 |
| Range of use/materials | Low suction capability [mm] | 10 |
| | Length of Power Cable [m] | 10 |
| | Cable | H05 RNF |
| | Pump International protection | IP X8 |
| | Insulation Class | B |
| | Liquid range Temperature [°C] | 0 °C / +35 °C |
| | Dimension of particles [mm] | Ø 30 |
| Dimensions / weight | Max. Ambient Temperature [°C] | +40 °C |
| | L x W x H [mm] | 205 x 150 x 245 |
| | L1 [mm] | 166.6 |
| | LM [mm] | 187.4 |
| | WM [mm] | 123.5 |
| | DNM GAS | 1" 1/4 F |
| | DNA GAS | 1" 1/4 F |
| | Box Dimensions l x w x h [cm] | 22,4 x 17,4 x 32 |
| | Net/Gross Weight [kg] | 4.65 / 5.6 |
| | Quantity for pallet [no.] | 72 |

